

### Description

Internal doors with a laminated timber core, made to order and available in a wide range of finishes. Various grades of fire and acoustic ratings available.

### Features

- Bespoke sizes
- Severe duty particleboard core
- Choice of facings and frames
- Vision panels available, apertures easy to cut and install
- Precision finished surface meets the highest requirements and is a suitable base for paint, delicate veneers, thin foils and laminates

### Typical applications

May be used as a general door core where heavier duty performances are required in most commercial, light industrial, educational, leisure and healthcare projects.

### Finishes

Primed/lacquered as delivered.

### Facings

- Veneer / Plywood / Laminate
- *Species:* Oak / Walnut / Ash / Maple / Steamed Beech / Cherry / Sapele / Koto / Eucalyptus / Not Applicable

### Fire resistance rating

Natradoor+LTC has been tested to BS 476, Part 22 for FD60 fire door applications.

### Sound insulation rating

With additional sealing Natradoor+LTC can provide for sound attenuating performances between  $R_w$  27dB and  $R_w$  33dB.

### Vision panel

*Dimensions:* As shown on door schedule

*Glazing:* Clear single glazing to suit fire resistance and sound insulation requirements

*Beading:*

- Material: Hardwood to match door leaf lipping
- Design: Standard bolection/flush
- Fixing method: Pinned

