

Description

Natraframe combined with Natradoor doors provide affordability and durability, whilst maintaining aesthetic appeal. Frames are available loose stop, rebated frame or split wrap-around version, and are adjustable to suit discrepancies in wall thicknesses.

Features

- Bespoke sizes
- Severe duty core
- Choice of facings and frames
- Vision panels available
- Precision finished surface meets the highest requirements and is a suitable base for paint, delicate veneers, and laminates

Finishes

FD30 Lining/frame material:

- Minimum 70mm x 30mm thick
- Softwood or hardwood
- 15 x 4 intumescent seals to frame perimeter

FD60 Lining/frame material:

- Minimum 80mm x 32mm thick
- Hardwood
- 2 no. 15 x 4 intumescent seals to frame perimeter

Frame materials and specifications

Natraframe LS:

Loose Stop Frame

- NFR/FD30/FD60
- Up to 42 dB
- Standard 32mm section with 32x12 stop
- Bespoke sections available

Natraframe RB:

Rebated Frame

- NFR/FD30/FD60
- Up to 42 dB
- Standard 44mm section with 12mm rebate
- Bespoke sections available

Natraframe WA:

Split wrap-around frame

- NFR/FD30/FD60
- Up to 42 dB.
- Standard 47mm section with 15x10mm wrap projection and 32x12 loose stop

